

Printing date 31.08.2020 Version number 15 Revision: 31.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Z117 Nano-Versiegelung
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Protective impregnation
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Lasala AG

Wehntalerstrasse 113

8105 Regensdorf

- · Further information obtainable from: info@lasala.ch
- · 1.4 Emergency telephone number:

Centre suisse d'information toxicologique, Zurich

+41 (0)44 251 51 51 ou 145 (depuis la Suisse)

Schweizerisches Toxikologisches Informationszentrum, Zürich

+41 (0)44 251 51 51 oder aus der Schweiz: Tel 145

Centro Svizzero d'informazione tossicologica

+41 (0)44 251 51 51 o dalla Svizzera: Tel 145

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07
- · Signal word Danger
- · Hazard-determining components of labelling: propan-2-ol
- · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P102 Keep out of reach of children.

(Contd. on page 2)

Printing date 31.08.2020 Version number 15 Revision: 31.08.2020

Trade name: Z117 Nano-Versiegelung

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	propan-2-ol	50-100%
CAS: 541-02-6 EINECS: 208-764-9 Reg.nr.: 01-2119511367-43	decamethylcyclopentasiloxane	5-10%
· SVHC 541-02-6 decamethylcyclope		

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

• **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Printing date 31.08.2020 Version number 15 Revision: 31.08.2020

Trade name: Z117 Nano-Versiegelung

(Contd. of page 2)

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with	limit values that r	eauire monitorins	g at the workplace:
1.10	***************************************	. 4	, and the month process

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

· DNELs

67-63-0 propan-2-ol

Oral	DNEL long term systemic effects	26 mg/kg bw/day (general population)
Dermal	DNEL long term systemic effects	319 mg/kg bw/day (general population)
		888 mg/kg bw/day (workers)
Inhalative	DNEL long term systemic effects	89 mg/m3 (general population)
		500 mg/m3 (workers)

· PNECs

67-63-0 propan-2-ol

PNEC	140.9 mg/i (intermittent release)
	2,251 mg/l (sewage plant)

PNEC aqua 140.9 mg/l (fresh water) 140.9 mg/l (sea water)

PNEC sediment 552 mg/kg (fresh water)

552 mg/kg (sea water)

PNEC ground 28 mg/kg (ground)

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Printing date 31.08.2020 Version number 15 Revision: 31.08.2020

Trade name: Z117 Nano-Versiegelung

(Contd. of page 3)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- Protection of hands:



Protective gloves

· Material of gloves

Rubber gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information of	basic physical	l and chemical	properties
----------------------	----------------	----------------	------------

General Information

· Appearance:

Form: Fluid
Colour: Colourless
Odour: Alcohol-like
Odour threshold: Not determined.

· pH-value at 20 °C:

· Change in condition

Melting point/freezing point: <0 °C Initial boiling point and boiling range: 82 °C

· Flash point: 13 °C

· Flammability (solid, gas): Not applicable.

• Ignition temperature: 385 °C

• **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 0.5 Vol %

 Upper: 12 Vol %

(Contd. on page 5)

Printing date 31.08.2020 Version number 15 Revision: 31.08.2020

Trade name: Z117 Nano-Versiegelung

	(Contd. c	of page
Vapour pressure at 20 °C:	43 hPa	
Density at 20 °C:	0.806g/cm^3	
Relative density	Not determined.	
· Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Easily soluble.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Organic solvents:	88.8 %	
Water:	0.0 %	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC5	· LD/LC50 values relevant for classification:	
67-63-0		
Oral	LD50	5,280 mg/kg (Rat)
Dermal	LD50	17,600 mg/kg (Rabbit)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

Printing date 31.08.2020 Version number 15 Revision: 31.08.2020

Trade name: Z117 Nano-Versiegelung

(Contd. of page 5)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

67-63-0 propan-2-ol

EC50 (48h) 13,299 mg/l (Daphnia magna)

LC50 (96h) 9,640 mg/l (Pimephales promelas)

- · 12.2 Persistence and degradability Easily biodegradable
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Γ	· European waste catalogue	
		MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
	20 01 00	separately collected fractions (except 15 01)
	20 01 29*	detergents containing hazardous substances

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

1 0	rmation
· 14.1 UN-Number · ADR, IMDG, IATA	UN1993
· 14.2 UN proper shipping name	
· ADR	1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANO
	(ISOPROPYL ALCOHOL))
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ISOPROPANC
	(ISOPROPYL ALCOHOL))

(Contd. on page 7)

Printing date 31.08.2020 Version number 15 Revision: 31.08.2020

Trade name: Z117 Nano-Versiegelung

(Contd. of page 6) · 14.3 Transport hazard class(es) · ADR, IMDG, IATA 3 Flammable liquids. · Class · Label · 14.4 Packing group · ADR, IMDG, IATA II14.5 Environmental hazards: · Marine pollutant: No Warning: Flammable liquids. · 14.6 Special precautions for user · Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-E· Stowage Category В · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code *Not applicable.* · Transport/Additional information: · Limited quantities (LQ) IL· Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category · Tunnel restriction code D/E· IMDG 1L· Limited quantities (LQ) Code: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL · UN "Model Regulation": (ISOPROPYL ALCOHOL)), 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 70
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

(Contd. on page 8)

Printing date 31.08.2020 Version number 15 Revision: 31.08.2020

Trade name: Z117 Nano-Versiegelung

(Contd. of page 7)

- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

541-02-6 decamethylcyclopentasiloxane

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* * Data compared to the previous version altered.

GB