Page 1/8



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.08.2020

Version number 19

Revision: 31.08.2020

*	SECTION 1: Identification of the substance/mixture and of the company/undertaking
	· 1.1 Product identifier
	• Trade name: <u>T66 Teppichschaum</u> • 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. • Application of the substance / the mixture Carpet shampoo
	• 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: Lasala AG Wehntalerstrasse 113 8105 Regensdorf
	<ul> <li>Further information obtainable from: info@lasala.ch</li> <li>1.4 Emergency telephone number: Centre suisse d'information toxicologique, Zurich</li> <li>+41 (0)44 251 51 51 ou 145 (depuis la Suisse) Schweizerisches Toxikologisches Informationszentrum, Zürich</li> <li>+41 (0)44 251 51 51 oder aus der Schweiz: Tel 145 Centro Svizzero d'informazione tossicologica</li> <li>+41 (0)44 251 51 51 o dalla Svizzera: Tel 145</li> </ul>
*	SECTION 2: Hazards identification · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008
	GHS02 flame
	Aerosol 1       H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
	Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
	<ul> <li>2.2 Label elements</li> <li>Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.</li> <li>Hazard pictograms GHS02</li> <li>Signal word Danger</li> <li>Hazard statements</li> </ul>
	H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H412 Harmful to aquatic life with long lasting effects.
	Precautionary statementsP102Keep out of reach of children.
	<ul> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P211 Do not spray on an open flame or other ignition source.</li> <li>P251 Do not pierce or burn, even after use.</li> </ul>
	P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	• Additional information: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not
	pierce or burn, even after use. Pasults of <b>PBT</b> and v <b>PvB</b> assessment
	• <i>Results of PBT and vPvB assessment</i> • <i>PBT:</i> Not applicable.
	(Contd. on page 2)

Page 2/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.08.2020

Version number 19

Revision: 31.08.2020

Trade name: T66 Teppichschaum

· vPvB: Not applicable.

(Contd. of page 1)

### **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane, pure ♦ Flam. Gas 1, H220; ♦ Acute Tox. 3, H331; Press. Gas (Comp.), H280	10-20%
EC number: 919-446-0 Reg.nr.: 01-2119471991-29	Naphtha (petroleum), heavy alkylate Flam. Liq. 3, H226; S Asp. Tox. 1, H304; Aquatic Chronic 2, H411	5-10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Tlam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-5%
CAS: 85711-69-9 EINECS: 288-330-3	Sulfonic acids, C13-17-sec-alkane, sodium salts Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

• 5.1 Extinguishing media

- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## **SECTION 6:** Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 3)

GR

Page 3/8

\*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.08.2020

Version number 19

Revision: 31.08.2020

Trade name: T66 Teppichschaum

(Contd. of page 2)

7.1 Preca	utions for safe handling
	od ventilation/exhaustion at the workplace.
	handle receptacle with care.
	on about fire - and explosion protection:
	ray onto a naked flame or any incandescent material.
	tion sources away - Do not smoke.
	ainst electrostatic charges. 2d container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electri
	not pierce or burn, even after use.
7.2 Condi	tions for safe storage, including any incompatibilities
Storage:	
	ents to be met by storerooms and receptacles:
	cool location.
	fficial regulations on storing packagings with pressurised containers. <b>on about storage in one common storage facility:</b> Not required.
	iformation about storage conditions:
	ainer tightly sealed.
Do not see	al receptacle gas tight.
	ool, dry conditions in well sealed receptacles.
	om heat and direct sunlight.
Storage cl	ass: 2 B ic end use(s) No further relevant information available.
Additiona	ON 8: Exposure controls/personal protection I information about design of technical facilities: No further data; see item 7.
Additiona 8.1 Contro	<b>l information about design of technical facilities:</b> No further data; see item 7. ol parameters
Additiona 8.1 Contro Ingredien	<b>l information about design of technical facilities:</b> No further data; see item 7. ol parameters ts with limit values that require monitoring at the workplace:
Additiona 8.1 Contro Ingredien 106-97-8	l information about design of technical facilities: No further data; see item 7. ol parameters ts with limit values that require monitoring at the workplace: butane, pure
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho	l information about design of technical facilities: No further data; see item 7. ol parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon	l information about design of technical facilities: No further data; see item 7. ol parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon Car	l information about design of technical facilities: No further data; see item 7. ol parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm c (if more than 0.1% of buta-1.3-diene)
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon Car Additiona	l information about design of technical facilities: No further data; see item 7. ol parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm c (if more than 0.1% of buta-1.3-diene) I information: The lists valid during the making were used as basis.
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon Car Additiona 8.2 Expos	l information about design of technical facilities: No further data; see item 7. ol parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm c (if more than 0.1% of buta-1.3-diene)
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon Car Additiona 8.2 Expos Personal	l information about design of technical facilities: No further data; see item 7. ol parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm c (if more than 0.1% of buta-1.3-diene) I information: The lists valid during the making were used as basis. ure controls
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon Car Additiona 8.2 Expos Personal p General p Wash han	l information about design of technical facilities: No further data; see item 7. of parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm c (if more than 0.1% of buta-1.3-diene) I information: The lists valid during the making were used as basis. ure controls protective equipment: rotective and hygienic measures: ds before breaks and at the end of work.
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon Car Additiona 8.2 Expos Personal p General p Wash han Do not inh	l information about design of technical facilities: No further data; see item 7. of parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm c (if more than 0.1% of buta-1.3-diene) I information: The lists valid during the making were used as basis. ure controls protective equipment: rotective and hygienic measures: ds before breaks and at the end of work. male gases / fumes / aerosols.
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon Car Additiona 8.2 Expos Personal p General p Wash han Do not inh Respirato	l information about design of technical facilities: No further data; see item 7. of parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm c (if more than 0.1% of buta-1.3-diene) l information: The lists valid during the making were used as basis. ure controls protective equipment: rotective and hygienic measures: ds before breaks and at the end of work. hale gases / fumes / aerosols. ry protection: Use suitable respiratory protective device in case of insufficient ventilation.
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon Car Additiona 8.2 Expos Personal p General p Wash han Do not inh Respirator Protection	l information about design of technical facilities: No further data; see item 7. ol parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm c (if more than 0.1% of buta-1.3-diene) I information: The lists valid during the making were used as basis. ure controls protective equipment: rotective and hygienic measures: ds before breaks and at the end of work. hale gases / fumes / aerosols. ry protection: Use suitable respiratory protective device in case of insufficient ventilation. a of hands: Not required.
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon Car Additiona 8.2 Expos Personal p General p Wash han Do not inh Respirator Protection Material of	l information about design of technical facilities: No further data; see item 7. ol parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm c (if more than 0.1% of buta-1.3-diene) I information: The lists valid during the making were used as basis. ure controls protective equipment: rotective and hygienic measures: ds before breaks and at the end of work. hale gases / fumes / aerosols. ry protection: Use suitable respiratory protective device in case of insufficient ventilation. of hands: Not required. of gloves Rubber gloves
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon Car Additiona 8.2 Expos Personal p Wash han Do not inh Respirator Protection Material o Penetratio The exact	l information about design of technical facilities: No further data; see item 7. ol parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm c (if more than 0.1% of buta-1.3-diene) I information: The lists valid during the making were used as basis. ure controls protective equipment: rotective and hygienic measures: ds before breaks and at the end of work. hale gases / fumes / aerosols. ry protection: Use suitable respiratory protective device in case of insufficient ventilation. a of hands: Not required.
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon Car Additiona 8.2 Expos Personal p General p Wash han Do not inh Respirato Protection Material o Penetratio The exact observed.	I information about design of technical facilities: No further data; see item 7. Of parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm c (if more than 0.1% of buta-1.3-diene) I information: The lists valid during the making were used as basis. ure controls protective equipment: rotective and hygienic measures: ds before breaks and at the end of work. hale gases / fumes / aerosols. ry protection: Use suitable respiratory protective device in case of insufficient ventilation. of hands: Not required. of gloves Rubber gloves m time of glove material break trough time has to be found out by the manufacturer of the protective gloves and has to b
Additiona 8.1 Contro Ingredien 106-97-8 WEL Sho Lon Car Additiona 8.2 Expos Personal p General p Wash han Do not inh Respirato Protection Material o Penetratio The exact observed.	l information about design of technical facilities: No further data; see item 7. ol parameters ts with limit values that require monitoring at the workplace: butane, pure rt-term value: 1810 mg/m <sup>3</sup> , 750 ppm g-term value: 1450 mg/m <sup>3</sup> , 600 ppm c (if more than 0.1% of buta-1.3-diene) I information: The lists valid during the making were used as basis. ure controls protective equipment: rotective equipment: rotective and hygienic measures: ds before breaks and at the end of work. hale gases / fumes / aerosols. ry protection: Use suitable respiratory protective device in case of insufficient ventilation. of hands: Not required. of gloves Rubber gloves on time of glove material

Printing date 31.08.2020

Version number 19

Revision: 31.08.2020

Trade name: T66 Teppichschaum

(Contd. of page 3)

	den inden ander
9.1 Information on basic physical and c General Information	cnemicai properties
Appearance:	
Form:	Aerosol
Colour:	White
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value at 20 °C:	-
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	2: <0 °C
Flash point:	<-20 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	354 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Not determined.
Explosion limits:	
Lower:	1.5 Vol %
Upper:	8.5 Vol %
Vapour pressure at 20 °C:	2,100 hPa
Density at 20 °C:	$0.95 \ g/cm^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Partly miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined. 15.0 %
Organic solvents: Water:	13.0 % 73.0 %
9.2 Other information	No further relevant information available.

#### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

 $\cdot$  10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 5)

GB

Printing date 31.08.2020

Version number 19

Revision: 31.08.2020

Trade name: T66 Teppichschaum

(Contd. of page 4)

### **SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (Rat)

## Naphtha (petroleum), heavy alkylate

Oral	LD50	>6,000 mg/kg (Rat)
Dermal	LD50	>3,000 mg/kg (Rabbit)

· Primary irritant effect:

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

- · Recommendation
- Must be specially treated adhering to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · European waste catalogue

16 00 00 WASTES NOT OTHERWISE SPECIFIED IN THE LIST

16 05 00 gases in pressure containers and discarded chemicals

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

(Contd. on page 6)

Page 6/8

\*

# Safety data sheet according to 1907/2006/EC, Article 31

Version number 19

Revision: 31.08.2020

(Contd. of page 5)

Trade name: T66 Teppichschaum

Printing date 31.08.2020

• Uncleaned packaging: • Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	
	UN1950
14.2 UN proper shipping name ADR IMDG, IATA	1950 AEROSOLS AEROSOLS
14.3 Transport hazard class(es) ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2 Gases.
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	Not applicable. JA
14.6 Special precautions for user Hazard identification number (Kemler code): Stowage Code	Warning: Gases. 23 SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clea
Segregation Code	of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Annex II Marpol and the IBC Code	of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity

Printing date 31.08.2020

Version number 19

Revision: 31.08.2020

Trade name: T66 Teppichschaum

	(Contd. of page 6)
• Transport category	2
• Tunnel restriction code	D
· IMDG	1L
· Limited quantities (LQ)	Code: E0
· Excepted quantities (EQ)	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

#### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• Seveso category P3a FLAMMABLE AEROSOLS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· National regulations:

· Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons

anionic surfactants

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas. H226 Flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H331 Toxic if inhaled. H411 Toxic to aquatic life with long lasting effects. · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas

(Contd. on page 8)

≥15 - <30%

<5%

<sup>-(</sup> 

Printing date 31.08.2020

Version number 19

Revision: 31.08.2020

#### Trade name: T66 Teppichschaum

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity - inhalation – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 • \* Data compared to the previous version altered. (Contd. of page 7)

GB